


PORTADECK



FOR BUOYANT, TEMPORARY ACCESS ACROSS SOFT GROUND AND EXTREME WET & COLD WEATHER CONDITIONS. PORTADECK IS THE ULTIMATE HEAVY DUTY MAT FOR TEMPORARY ROAD & EQUIPMENT STAGING AREA

www.mtandt.com

Toll Free: 1800 200 8088



ABOUT US

A legacy that continues to scale new heights

Mtandt is a leading provider of technology and solutions to diversified industry through manufacturing, distribution, renting, training and services.



Mtandt Makes Your Work SAFE & EASY

Manufacturing | Sales | Rental | Service | Training | Certification



PORTADECK

Mtandt Group has been leading the field of delivering innovative solutions. Our latest introduction of PORTADECK range of temporary access and Ground stabilization mats, developed after years of experience in providing solutions for more extreme weather and ground conditions.



UNIQUE SELLING PROPOSITION

- Compressive strength more than 425 tons/m² reaching max 730 ton/m²
- Unique both side traction surface, suitable for tyre & metal tracks
- Foam field core to prevent water incursion

EASY TO INSTALL

Easy to fix metal ramp available as an option for smooth movement of vehicles



SAFETY PRODUCTIVITY CONVENIENCE


SAFETY AND EFFICIENCY

Engineered for performance and strength, the interlocking mats distribute weight across a large surface area, while remaining stable and strong through all weather conditions. The tread pattern improves safety and traction for load-bearing vehicles, while the interlocking system reduces the chance for drift and slippage. The mats provide years of reusable performance and an endless shelf- life with proper use and maintenance.

General Information	
Dimension	94 x 2000 x 4000 mm
Weight	360kg
Color	Beige (standard)
Logistic	Standard high cube container 50 pcs, truck standard 56 pcs
Handling	Designed for end users, 2-sided mat for different type of vehicles (Tyre or Metal track)
Recycling	100% recyclable
Environmental	No moisture absorption, allows decontamination - cleaning
Safety	Nub structure prevents slips, trips, falls
Bearing capacity	425 Ton/m² (605 psi)
Fire rating	UL 94HB



PERFORMED TESTS ON GROUND MATS



FEA Analyses

It shows that the product will Perform the way it has Been design.



TESTS CONDUCTED

3 POINT LOAD TEST

Tested at an applied force of 27.93 kN And mid-span deflection of 133mm.



COMPRESSION TEST



CYCLING MAT TEST

No breakage up to total 1,00,000 Cycles.



TEMPERATURE TEST

Tested at -40 to +55 C



BENDING TEST

Bending Tests at Ambient Temperature











A WIDE NETWORK

for a quick answer



OUR REACH AND DISTRIBUTION NETWORK

Mtandt's experience and global reach make us uniquely qualified to fulfil all your needs. We provide you with on time delivery of your products and follow it up with assistance, support and training. To know in detail about our products and services, get in touch with Team Mtandt now!

You can also find us at: DUBAI - SRI LANKA - NEPAL - BHUTAN - BANGLADESH

Mtandt Limited

Communication Address:

17/8, West Mada Church Road, Royapuram, Chennai, Tamil Nadu - 600 013. India.

Phone: +91 44 4263 2500

South:

62/2B, New No.99, Old No.144, Padur Village, Poonamalle Taluk, Thiruvallur Dist, Chennai, Tamil Nadu - 602 105. India.

North:

Plot: - A-34/1, Site-IV, Industrial Area, Sahibabad, Ghaziabad, 201010, U.P., India. Phone: +91 0120 47 32 231

West:

Plot No. A-311/A-312, T.T.C. Industrial Area, M.I.D.C., Mahape, Navi Mumbai, Maharashtra - 400701, India. Cell + 91 77188 97739

marketing@mtandt.com | www.mtandt.com | Toll Free: 1800 200 8088